

# DECLARATION OF PERFORMANCE

SalzLBasic-CRP-2017/02/24-GB



## PRODUCT

**Product type** Slow heat release appliance  
**Type designation** Salzburg L Basic; Salzburg L+1 Basic  
**Product identification** See product instruction manual  
**Intended area of use** Heating of rooms in residential buildings  
**Fuel** Wood

## MANUFACTURER

**Name** Nordpeis AS  
**Adress** Gjellebekkstubben 11  
3420 Lierskogen, Norway

## CHECKS

**According to AVCP** System 3  
**Standard** EN 15250:2007  
**Test institute** Rein-Ruhr Feuerstatätten Prüfstelle, NB 1625  
has checked declared performance and issued test report no. RRF- 50 16 4448

## DECLARED PERFORMANCE

Essential Characteristic	Performance	Harmonized technical specification
Reaction to fire	A1 WT	EN 15250:2007
Minimum distances to combustible material	50 mm rear 300 mm side other safety distances according product manual	
Risk of falling embers	Approved	
Emission from combustion: Carbon monoxide at 13% O <sub>2</sub> Oxygen nitride NO <sub>x</sub> at 13% O <sub>2</sub> Organic Gaseous Carbon at 13% O <sub>2</sub> Particulate Matter at 13 O <sub>2</sub>	CO = 0,070 % Vol NO <sub>x</sub> = 118 mg / m <sup>3</sup> OGC = 75 mg / m <sup>3</sup> PM = 23 mg / m <sup>3</sup>	
Surface temperatures	Approved	
Cleanability	Approved	
Mechanical durability	Approved	
Releases of Hazardous Substances	Approved	
Total thermal output	45,14 kWh	
Nominal output after elapsed time at 25% of max. mean temperature	P = 2,00 kW	
Flue gas temperature at nominal output	t <sub>a</sub> = 113 °C	
Energy efficiency	η = 90,0 %	

The undersigned is responsible for the manufacture and conformity with declared performance



Stian Varre, CEO Nordpeis AS